



8000VA



# SOLAR INVERTER

- IP54 certified enclosure
- Dual outputs, for smart load management
- Reserved communication port for BMS (RS485, CAN-BUS or RS232)
- Replaceable fan design for ease of maintenance
- Battery independent design
- Configurable AC/PV output usage timer and prioritization
- Selectable high power charging current
- Selectable input voltage range for home appliances and personal computers
- Compatible to Utility Mains or generator input
- Parallel operation up to 6 units



## Solar Inverter Specifications

<b>MODEL</b>	<b>X6-8012-S2</b>
<b>RATED POWER</b>	8000VA/8000W
<b>PARALLEL CAPABILITY</b>	YES, 6 units
<b>INPUT</b>	
Voltage	230 VAC MAX-300 VAC
Selectable Voltage Range	170-280 VAC (For Computers) 90-280 VAC (For Home Appliances)
Frequency Range	50 Hz/60 Hz (Auto sensing)
<b>OUTPUT</b>	
AC Voltage Regulation (Batt. Mode)	230VAC $\pm$ 5%
Surge Power	16000VA
Efficiency (Peak)	93%
Transfer Time	10 ms (For Personal Computers), 20 ms (For Home Appliances)
Waveform	Pure sine wave
No Load Power Consumption	< 85W
<b>BATTERY</b>	
Battery Voltage	48 VDC
Floating Charge Voltage	54 VDC
Overcharge Protection	66 VDC
<b>SOLAR CHARGER &amp; AC CHARGER</b>	
Solar Charger Type	MPPT
Maximum PV Array Power	8000W (4000W x 2)
MPPT Range @ Operating Voltage	90 ~ 450 VDC
Maximum PV Array Open Circuit Voltage	500 VDC
Maximum PV Input Current	15 A x 2
Maximum Solar Charge Current	150 A
Maximum AC Charge Current	120 A
Maximum Charge Current	150 A
<b>PHYSICAL</b>	
Dimension, D x W x H (mm)	210 x 435 x 665
Net Weight (kgs)	32
Communication Interface	USB/RS-232/Dry Contact/RS485/WiFi/BMS
<b>OPERATING ENVIRONMENT</b>	
Humidity	5% to 95% Relative Humidity (Non-condensing)
Operating Temperature	-10°C to 50°C
Storage Temperature	-15°C to 60°C
<b>STANDARD</b>	
Compliance Safety	CE

Product specifications are subject to change without further notice.