

Powerwall 4.15 25.6V100AH



Model: LIO 3.84



IP54
Protection



4.3" HMI
Touchable
Screen



1.5C
Continuous
Charge / Discharge



6000
Cycles



5 Years
Warranty



100AH
Capacity



LiFePO4
Cells



PAGE BMS



Parallel
upto 4 Units

- A grade brand new prismatic LiFePO4 cells
- 6000 cycles @80% DOD (25°C, 0.5C)
- Over charge, over discharge, over temperature, low temperature, over current and short circuit protection
- HMI touchable screen with low power consumption, high brightness, and long visual distance.
- Cell balance function
- Metal Case, excellent heat dissipation, more safety
- Certificate: UN38.3, MSDS
- Max 4 battery packs can be connected in parallel

Compatible with Inverter Brands



Many More.....

Technical Data Sheet

MODEL	LIO 3.84
ELECTRICAL PARAMETER	
Battery Type	LiFePO4
Nominal Voltage (V)	25.6
Nominal Capacity (AH)	100
Energy (WH)	2560
Pack Mode	8S1P
Continuous Discharge Current (A)	150
Charge Cut-off Voltage (V)	28.8
Discharge Cut-off Voltage (V)	20.8
Max. Charge Current (A)	100
Max. Discharge Current (A)	150
Peak Discharge Current (A)	180
Recommend Discharge Current (A)	50
Recommend Discharge Depth (%)	80
Cycle Life	> 6000 cycles (25°C, 0.5C) @ 80% DOD
Function	---
Communication	RS485
Display	HMI Touchable
Mounting	Wall-mounted
ENVIRONMENTAL PARAMETER	
Charge & Discharge Temperature (°C)	Charge: 0°C ~ +55°C / Discharge: -20°C ~ +60°C
Optimal Storage Temperature (°C)	5°C ~ +35°C
Relative Humidity	40% ~ 80%
Ingress Protection	IP54
MECHANICAL PARAMETER	
Terminal	Quick Plug
Dimensions (L*W*H) (mm)	350*180*450
Weight (Kg)	25.6 ± 0.5
Certificate	UN38.3 MSDS