

Lithium-ion Battery

Rackwall 8 51.2V150AH



Model:
LIO 8.0-IP20



IP20
Protection



4.3" HMI
Touchable
Screen



Continuous
Charge / Discharge



6000
Cycles



5 Years
Warranty



150AH
Capacity



Powered by
REPT



LiFePO4
Cells



PACE BMS



Parallel
upto 15 Units



Safety

- Long life type prismatic LiFePO4 cells, suitable for energy storage application.
- Low voltage system, safety for application.
- Battery certification: UN38.3, MSDS, CE



Scalability

- Parallel support for more energy.
- Communication compatible with the major inverter manufacturers, Change different inverter protocol by LCD.



Design

- Standard 19" rack design.
- Flexible and easily installation, rack mounted.
- -20~+55°C widely temperature range.
- 4.3" touch LCD screen.
- Quick Lock and Press-to-Release Terminals.
- Maintenance free.



Battery Management System

- Independent protection for charge and discharge.
- SOC, Alarm, Run display and PC software for detailed operation.
- OVP, LVP, OCP, OTP, LTP, Short-circuit protection.
- RS485, CAN communication port for inverter and Link in & out for battery to battery communication.

Technical Data Sheet

Model	LIO 8.0-IP20
Nominal Voltage [V]	51.2
Nominal Capacity [Ah]	150
Total Energy [Wh]	7680
Dimension (W*D*H, mm)	442*520*175
Weight [Kg]	65.0
Max. Charging Current [A]	150
Max. Discharging Current [A]	150
Pulse Discharge Current	180A @2S
Charging Voltage [V]	55.2-57.6
End of Discharge Voltage [V]	44
Operation Humidity	0-95% RH (No condensing)
Operating Temperature Range	Charge: 0 ~ +55°C; Discharge: -20 ~ +55°C
Cycle Life ⁽¹⁾	>5000
Designed Calendar Life	10 Years
Communication interface	For inverter : RS485, CAN For battery to battery: LINK-IN, LINK-OUT
Protection	Over voltage, Low voltage, Over current, Over Temperature, Low Temperature, Short circuit
Parallel Support ⁽²⁾	Yes, Max. 15 Sets
Series Support	Not support

Note:

(1) 25°C, 0.5C /1C , 90%DOD to 80% of initial capacity.

(2) For parallel connection, refer to user manual.

Compatible with Inverter Brands

